

# REVOLVE® S-TeQ PA 12

Polyamide 12

Matrix Polymers

## Message:

Revolve S-TeQ PA12 is a rotational moulding polyamide 12 (Nylon) with enhanced impact properties. The grade carries the inherent PA12 characteristics such as chemical resistant and low permeation to hydrocarbons. The grade exhibits good stiffness, high temperature resistance and good mouldability.

General Information			
Features	Good Chemical Resistance		
	Good Impact Resistance		
	Good Moldability		
	High Hardness		
	High Heat Resistance		
	High Stiffness		
Appearance	Natural Color		
Forms	Powder		
Processing Method	Rotational Molding		
Physical	Nominal Value	Unit	Test Method
Density	1.01	g/cm <sup>3</sup>	ISO 1183
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Yield)	31.0	MPa	ISO 527-2/50
Flexural Modulus <sup>1</sup>	1250	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
ARM Impact (23°C, 3.00 mm)	95.0	J	
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (0.45 MPa, Unannealed)	80.0	°C	ISO 75-2/B
NOTE			
1.	1.3 mm/min		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT