

# Manner Flexible PVC M1496

Flexible Polyvinyl Chloride

Manner Plastics, L.P.

Message:

Recommended Applications: Lead-free general purpose injection molding compound. Manner M1496 is UL recognized under QMFZ8 and QMFZ2. This product complies with the European Union Restriction on Hazardous Substances (RoHS) directive.

General Information			
UL YellowCard	E107449-542554		
Uses	Consumer Applications		
	Electrical/Electronic Applications		
	Footwear		
Agency Ratings	UL 94		
	UL QMFZ2		
	UL QMFZ8		
RoHS Compliance	RoHS Compliant		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.42 to 1.46	g/cm <sup>3</sup>	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore C)	75 to 81		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (100% Strain, 1.52 mm)	11.2	MPa	ASTM D638
Tensile Strength (Yield, 1.52 mm)	12.6	MPa	ASTM D638
Tensile Elongation (Break, 1.52 mm)	200	%	ASTM D638

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT