

PRIMALENE WPP733P

High Density Polyethylene

Southern Polymer, Inc.

Message:

A film grade high density polyethylene

Applications:

Moisture sensitive packaging

Food packaging

Blends

Coextrusions

Release liners

Features:

Excellent MVTR

Improved stiffness properties

Improved scuff resistance

Good processability

Low gel levels

FDA 21 CFR 177.1520 (c) 3.2a

General Information			
Features	Food Contact Acceptable		
	Good Processability		
	High Density		
	Low Gel		
Uses	Blending		
	Film		
	Food Packaging		
	Food Service Applications		
	Liners		
	Non-specific Food Applications		
	Packaging		
Agency Ratings	FDA 21 CFR 177.1520(c) 3.2a		
Processing Method	Coextrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.962	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	8.0	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

