

# TOTAL Polyethylene HDPE 2007 TN61

High Density Polyethylene

TOTAL Refining & Chemicals

## Message:

HDPE 2007 TN61 is a high density polyethylene (HDPE) intended for the extrusion of corrugated pipes.

HDPE 2007 TN61 is characterized by its high stiffness and its high Melt Flow Rate.

HDPE 2007 TN61 is best processed between 190 and 230°C

General Information	
Features	High Density High Flow High Stiffness
Uses	Piping
Agency Ratings	EC 1907/2006 (REACH)
Processing Method	Extrusion Pipe Extrusion

Physical	Nominal Value	Unit	Test Method
Density	0.961	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/21.6 kg)	52	g/10 min	ISO 1133

  

Thermal	Nominal Value	Unit
Melting Temperature	190 to 230	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

