

Gravi-Tech™ GT6000-5002 white 1

Polyamide 6
PolyOne Corporation

Message:

Gravi-Tech™ GT6000-5002 white 1 is a Polyamide 6 (Nylon 6) product. It can be processed by injection molding and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Applications of Gravi-Tech™ GT6000-5002 white 1 include appliances, automotive, consumer goods, engineering/industrial parts and handles. Primary characteristic: non-toxic.

General Information			
Features	High Specific Gravity		
	Non-Toxic		
Uses	Appliance Components		
	Automotive Applications		
	Consumer Applications		
	Handles		
	Industrial Applications		
	Knobs		
	Medical/Healthcare Applications		
	Metal Replacement		
	Sporting Goods		
	Weighting & Balancing		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	2.70	g/cm ³	ISO 1183
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	8000	MPa	ISO 527-2
Tensile Stress (Break)	70.0	MPa	ISO 527-2
Tensile Strain (Break)	1.5	%	ISO 527-2
Flexural Modulus	6100	MPa	ISO 178
Flexural Stress	80.0	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Charpy Notched Impact Strength	5.0	kJ/m ²	ISO 179
Charpy Unnotched Impact Strength	23	kJ/m ²	ISO 179
Injection	Nominal Value	Unit	
Drying Temperature	80.0	°C	
Drying Time	4.0	hr	
Processing (Melt) Temp	260 to 290	°C	
Mold Temperature	50.0 to 90.0	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

