

Fainplast PVC GS 6612

Polyvinyl Chloride

Fainplast Compounds S.r.l

Message:

Fainplast PVC GS 6612 is a Polyvinyl Chloride product. It can be processed by injection molding and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Typical application: Consumer Goods.

General Information			
Uses	Footwear		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	1.24	g/cm ³	ISO 1183
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	66		ISO 868
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break)	> 7.00	MPa	ISO 527-2
Tensile Strain (Break)	> 250	%	ISO 527-2
Thermal	Nominal Value	Unit	Test Method
Cold Flexibility	-35	°C	ISO 458/2

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

