

HANWHA P-1000

Polyvinyl Chloride

Hanwha Chemical

Message:

Feature: Fast melting and excellent work safety. Good for general soft material and hard material products

Use: Film sheet, leather, pipe, plate, sash not toxic sheet and corrugated plate

| General Information | | | |
|--|-------------------|-------------------|-----------------|
| Features | General Purpose | | |
| Uses | Piping | | |
| | Sheet | | |
| | Synthetic Leather | | |
| Physical | Nominal Value | Unit | Test Method |
| Apparent Density | 0.51 to 0.59 | g/cm ³ | ASTM D1895 |
| Particle Size - 42Mesh(350µm) Sieve Pass % | 100 | % | Internal Method |
| Volatile Matter | < 0.30 | % | ASTM D3030 |
| Degree of Polymerization | | | |
| DP | 950 to 1050 | | JIS K6720-2 |
| K-Value | 66.0 | | DIN 53726 |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT