# CoREZYN® CORVE8300-35

### Vinyl Ester

#### Interplastic Corporation

#### Message:

CoREZYN® vinyl ester resins are corrosion resistant to withstand severe environments. In addition, they enhance composites with high-strength, low-weight and excellent resistance to fatigue. That's why our vinyl esters have become the material of choice for many specialized applications, including fire resistance, in industries such as marine, transportation, construction, aerospace and others.

| General Information              |                                    |      |
|----------------------------------|------------------------------------|------|
| Features                         | Good Corrosion Resistance          |      |
|                                  | High Viscosity                     |      |
|                                  | Medium Reactivity                  |      |
|                                  |                                    |      |
| Uses                             | Aerospace Applications             |      |
| Construction Applicat            |                                    |      |
|                                  | Marine Applications                |      |
|                                  |                                    |      |
| Additional Information           | Nominal Value                      | Unit |
| Gel to Peak                      | 1.5 to 4.0                         | min  |
| Non-Volatile Content             | 62 to 67                           | %    |
| Peak Exotherm                    | 171 to 199                         | °C   |
| Uncured Properties               | Nominal Value                      | Unit |
| Viscosity (25°C, Brookfield HBT) | 2.2 to 2.8                         | Pa·s |
| Gel Time <sup>1</sup>            | 12 to 16                           | min  |
| NOTE                             |                                    |      |
|                                  | SPI gel time run in 180°F (82°C)   |      |
|                                  | water bath, catalyzed with 1.0 phr |      |
| 1.                               | of 98% benzyol peroxide, minutes.  |      |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

