

POLYFLON™ F-201L

Polytetrafluoroethylene

DAIKIN AMERICA, INC.

Message:

Daikin-Polyflon PTFE F-201L is a polytetrafluoroethylene fine powder resin for paste extrusion. F-201L has been designed with low extrusion pressure for spaghetti tubing, thin wall tubing and wire coating applications of less than 16 AWG that are run at high reduction ratios.

General Information			
UL YellowCard	E167420-225064		
Uses	Wire sheath		
	Pipe fittings		
Appearance	White		
Forms	Powder		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	2.16 - 2.20	g/cm ³	ASTM D4895
Apparent Density	> 0.40	g/cm ³	ASTM D4895
Particle Size	400 - 650	μm	ASTM D4895
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	> 25.0	MPa	ASTM D4895
Tensile Elongation (Break)	> 350	%	ASTM D4895
Extrusion instructions			

Extrusion Pressure: 540 to 650 kg/cm²

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT