

# Luxus PP 16174

Polypropylene  
Luxus Limited

Message:

Luxus PP 16174 is a Polypropylene material filled with 11% talc. It is available in Europe. Primary attribute of Luxus PP 16174: Eco-Friendly/Green.

General Information			
Filler / Reinforcement	Talc,11% Filler by Weight		
Recycled Content	Yes		
Appearance	Black		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	20 to 25	g/10 min	ISO 1133
Ash Content (650°C)	15000	mm	
Drying Temperature	80	°C	
Drying Time	2.0	hr	
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact Strength (23°C)	6.0 to 12	kJ/m²	ISO 180
Multi-Axial Instrumented Impact Peak Force	800 to 1000	N	ISO 527

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT