

Allen ABS Luran® 776/LXS

Acrylonitrile Butadiene Styrene
SEKISUI Polymer Innovations, LLC

Message:

Luran® 776/LXS is high impact ABS capped with low gloss ASA for UV protection.

Common Applications:

Vehicle Exteriors

Marine Parts

Radomes

Features and Benefits:

Custom color matching

Excellent UV properties

Edge trim easily used into future orders

low gloss finish

General Information			
Features	Good Impact Resistance		
	Good UV Resistance		
	Good Weather Resistance		
	Low Gloss		
Uses	Automotive Applications		
	Marine Applications		
Processing Method	Sheet Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.02 to 1.04	g/cm ³	ASTM D792
Molding Shrinkage - Flow	0.50 to 0.70	%	ASTM D955
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	34.5	MPa	ASTM D638
Flexural Modulus	1970	MPa	ASTM D790
Flexural Strength	55.2	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
-18°C	80	J/m	
23°C	350	J/m	
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	90.6	°C	ASTM D648
Flammability	Nominal Value		Test Method
Flame Rating (1.52 mm)	HB		UL 94
Optical	Nominal Value		Test Method
Gloss (60°)	30 to 50		ASTM D523

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519
Phone: +86 13424755533
Email: sales@su-jiao.com
No. 215, Lianhe North Road, Fengxian District, Shanghai, China

