BUSTREN® PS 184

General Purpose Polystyrene LUKOIL Bulgaria Ltd.

Message:

Granulated homopolymer of styrene with increased flowability and normal heat resistance. For production of various articles, including children's toys.

General Information			
Features	High Flow		
	Homopolymer		
Uses	General Purpose		
	Toys		
Appearance	Clear/Transparent		
Forms	Pellets		
Processing Method	Sheet Extrusion		
	Vacuum Forming		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) ¹ (200°C/5.0			
kg)	9.0 to 12	g/10 min	ASTM D1238
Moisture Content	< 0.20	%	Internal Method
Volatile Matter	< 0.80	%	Internal Method
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	> 15	J/m	ASTM D256A
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	> 84.0	°C	ASTM D1525
NOTE			
1.	Procedure A		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

