# YUNGSOX® PP 1124H

### Polypropylene Homopolymer

## Formosa Polypropylene

#### Message:

YUNGSOX® PP 1124H is a Polypropylene Homopolymer (PP Homopolymer) material. It is available in Asia Pacific. Important attributes of YUNGSOX® PP 1124H are:

Flame Rated

Heat Resistant

Food Contact Acceptable

**Good Aesthetics** 

**High Stiffness** 

Typical applications include:

**Appliances** 

Containers

**Food Contact Applications** 

**Household Applications** 

General Information					
UL YellowCard	E216959-464616				
Features	Food Contact Acceptable				
	Good Abrasion Resistance				
	Good Heat Aging Resistance				
	Good Surface Finish				
	High Heat Resistance				
	High Stiffness				
	Homopolymer				
Uses	Appliances				
	Containers				
	Household Goods				
Agency Ratings	FDA 21 CFR 177.1520				
UL File Number	E216959				
Forms	Pellets				
Physical	Nominal Value	Unit	Test Method		
Density	0.910	g/cm³	ISO 1183		
Melt Mass-Flow Rate (MFR) (230°C/2.16					
kg)	15	g/10 min	ISO 1133		
Molding Shrinkage	1.3 to 1.7	%	Internal Method		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	115		ISO 2039-2		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Stress (Yield)	48.1	МРа	ISO 527-2		
Tensile Strain (Break)	50	%	ISO 527-2		

Flexural Modulus	2160	MPa	ISO 178
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	29	J/m	ISO 180
Thermal	Nominal Value	Unit	Test Method
Heat Deflection Temperature (1.8 MPa, Unannealed)	135	°C	ISO 75-2/A
Vicat Softening Temperature	157	°C	ISO 306
RTI Elec	125	°C	UL 746
RTI Imp	125	°C	UL 746
RTI Str	125	°C	UL 746
Flammability	Nominal Value		Test Method
Flame Rating	НВ		UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

#### Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

