

Propilven F-651

Polypropylene Random Copolymer

Propilven, S.A.

Message:

Propilven F-651 grade is a random copolymer mainly designed as a sealing layer of medium SIT for bi-oriented and cast film. It can be used as a unique material or mixed with a tubular water quenched film (TQW).

Special Features:

Slip and anti-blocking agents

Medium SIT

Good clarity and birhtness

General Information			
Additive	Antiblock		
	Slip		
Features	Antiblocking		
	Food Contact Acceptable		
	Medium Clarity		
	Random Copolymer		
	Slip		
Uses	Cast Film		
	Film		
Forms	Pellets		
Processing Method	Cast Film		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR)	7.0	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	20.0	MPa	ASTM D638
Flexural Modulus	900	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	65	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	80.0	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

