

Colorite Rigid PVC 2602F CLR

Rigid Polyvinyl Chloride

Colorite Polymers

Message:

Colorite Rigid PVC 2602F CLR is a Rigid Polyvinyl Chloride product. It can be processed by blow molding or profile extrusion and is available in Asia Pacific, Europe, or North America. Applications of Colorite Rigid PVC 2602F CLR include bottles, food contact applications and packaging. Characteristics include:

Clarity
High Flow
High Gloss
Impact Resistant

General Information	
Features	Heat Stabilized
	High Clarity
	High Flow
	High Gloss
	High Impact Resistance
Uses	Bottles
	Packaging
	Profiles
Agency Ratings	FDA 21 CFR 178.2010
Appearance	Colors Available
Processing Method	Blow Molding
	Profile Extrusion

Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.32	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	76		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength	45.5	MPa	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	1200	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	162	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT