

HANWHA KH-60

Polyvinyl Chloride

Hanwha Chemical

Message:

Feature: Low viscosity and high transparency. Excellent water whitening resistance. Excellent autoclave applications

Use: Highly transparent label, flooring wall paper, leather top coatings, tarpaulins and rotational forming

General Information			
Features	Low viscosity		
	Good color stability		
	High pressure heating resistance		
Uses	Label		
	Floor Material		
	Coating application		
Appearance	Clear/transparent		
Physical	Nominal Value	Unit	Test Method
Apparent Density	0.19 - 0.27	g/cm ³	ASTM D1895
Volatile Matter		%	ASTM D3030
Particle size-100Mesh(150μm) Sieve Pass%	100	%	Internal method
Brokfield viscosity-cps/6rpm			ASTM D1824
degree of polymerization			
DP	1600 - 1800		JIS K6720-2
K-Value	76.0		DIN 53726
Additional Information	Nominal Value	Test Method	
Liquidity: Dilatant			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT