

# Jam HDPE HF7750M

High Density Polyethylene  
Jam Petrochemical Company

Message:

Jam HDPE HF7750M is a High Density Polyethylene product. It is available in Africa & Middle East. Typical application: Fabrics/Fibers.

General Information			
Uses	Monofilaments		
Physical	Nominal Value	Unit	Test Method
Density	0.956 to 0.960	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	22 to 28	g/10 min	ISO 1133
Flow Rate Ratio <sup>1</sup>	8.00 to 12.0		
Fish Eye	< 5.00		

NOTE			
1.	5/2.16, FRR values are statistical and calculated by dividing MFR values.		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT