

METALCAP PL380Z81

High Density Polyethylene

Polyram Ram-On Industries

Message:

81% MINERAL FILLED, HEAVY DENSITY POLYETHYLENE FOR INJECTION MOULDING METALLIZED PART AND GALVANIZED COVERS.

General Information			
Filler / Reinforcement	Mineral,81% Filler by Weight		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	3.00	g/cm ³	ASTM D792, ISO 1183
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	15	g/10 min	ASTM D1238, ISO 1133
Molding Shrinkage			
Flow	0.30	%	ASTM D955
--	0.30	%	ISO 2577

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT