

Hyundai EP Breathable AT880/2102

Polyolefin

HYUNDAI EP Co., Ltd.

Message:

Hyundai EP Breathable AT880/2102 is a Polyolefin product. It is available in Asia Pacific. Typical application: Medical/Healthcare. Primary characteristic: good processability.

| General Information | | | |
|---|---------------------|----------|-----------------|
| Features | Good Processability | | |
| Uses | Personal Care | | |
| Forms | Pellets | | |
| Physical | Nominal Value | Unit | Test Method |
| Melt Mass-Flow Rate (MFR) (190°C/2.16 kg) | 2.1 | g/10 min | ASTM D1238 |
| Ash Content | 29.0 | wt% | Internal Method |
| Moisture Content | < 0.10 | wt% | Internal Method |
| Fish Eye | < 20.0 | | Internal Method |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co., Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

