

Beamset 502H

Polyurethane

Arakawa Chemical Industries, Ltd.

Message:

This resin is a photo-curable resin that quickly and three-dimensionally cures by radical polymerization that occurs with electron beam (EB) or ultraviolet ray (UV) irradiation. This resin has been used widely for various applications.

Type:

Urethane acrylate

Characteristics:

Flexibility

Good adhesion

Use:

Adhesive (Good adhesion to PVC)

General Information		
Features	Good Adhesion	
	Good Flexibility	
Uses	Adhesives	
Appearance	Transparent - Slight Yellow	
	Yellow	
Forms	Liquid	
Additional Information	Nominal Value	Unit
Functionality	2.00	
Non-Volatile Content	100	%
Uncured Properties	Nominal Value	Unit
Viscosity (25°C)	120 to 180	Pa·s

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT