## **NEXT SIGNATURE POMC HF-300**

## Acetal (POM) Copolymer

NEXT Specialty Resins, Inc.

## Message:

NEXT SIGNATURE POMC HF-300 is an Acetal (POM) Copolymer material. It is available in North America.

Important attributes of NEXT SIGNATURE POMC HF-300 are:

Copolymer

Fast Molding Cycle

**Good Processability** 

High Flow

Typical applications include:

**Appliances** 

Electrical/Electronic Applications

General Information			
Features	Copolymer		
	Fast Molding Cycle		
	Good Moldability		
	High Flow		
Uses	Appliance Components		
	Electrical/Electronic Applications		
Appearance	Black		
Forms	Pellets		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.41	g/cm³	ASTM D792
Melt Mass-Flow Rate (MFR)	9.0	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (M-Scale)	80		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	2240	МРа	ASTM D638
Tensile Strength	58.6	MPa	ASTM D638
Tensile Elongation (Break)	30	%	ASTM D638
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	53	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (1.8 MPa, Unannealed)	107	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

