

# Hanwha Total PP TB1010

Polypropylene

HANWHA TOTAL PETROCHEMICALS Co., Ltd.

Message:

TB1010 is a 10% talc filled high-crystalline polypropylene low-pressure injection grade designed for superior fluidity. Due to superb flexural modulus and impact strength, this grade is suitable for the large- or thin-membrane part forming.

General Information			
Filler / Reinforcement	Talc,10% Filler by Weight		
Features	Crystalline		
	Good Impact Resistance		
	Good Weather Resistance		
	High Heat Resistance		
Uses	Automotive Interior Trim		
Forms	Pellets		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	1.00	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	80	g/10 min	ASTM D1238
Molding Shrinkage - Flow	1.2 to 1.6	%	ASTM D955
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	98		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	27.5	MPa	ASTM D638
Tensile Elongation (Break)	15	%	ASTM D638
Flexural Modulus	2260	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
-30°C	29	J/m	
23°C	49	J/m	
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	135	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

# Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

