

INEOS Wire & Cable B24D230

Ethylene Butyl Acrylate Copolymer

INEOS Olefins & Polymers Europe

Message:

B24D230 is an unstabilised copolymer of ethylene and butyl acrylate containing 8 % butyl acrylate. It is designed for compounding within wire & cable applications. It can accept high amounts of fillers and could be used as base polymer for a Flame Retardant Compound.

General Information			
Features	Copolymer		
Uses	Wire and cable applications		
	Composite		
RoHS Compliance	Contact manufacturer		
Forms	Particle		
Physical	Nominal Value	Unit	Test Method
Density	0.924	g/cm ³	ISO 1183/D
Melt Mass-Flow Rate (MFR) (190°C/0.325 kg)	0.35	g/10 min	ISO 1133
Additional Information			

Butyl Acrylate content: 8%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

