

Zeoforte® ZSC 2195CX

Acrylonitrile Butadiene Rubber

Zeon Chemicals L.P.

Message:

Nano-Composite Hydrogenated Nitrile Rubber - Zeon Super Composite

Main Characteristics & Applications

Highly saturated Zetpol composite with outstanding mechanical properties at high hardness. CX grades designed for maximum dynamic performance.

General Information		
Features	High Hardness	
Physical	Nominal Value	Unit
Specific Gravity	1.24	g/cm ³
Mooney Viscosity (ML 1+4, 100°C)	80 to 110	MU
Bound Acrylonitrile ¹	36.0	wt%
Iodine Value ²	11.0	mg/100 mg
NOTE		
1.	Measured on base polymer.	
2.	Measured on base polymer.	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT