

TRYCITE™ 8002.600

Polystyrene Film
The Dow Chemical Company

Message:

TRYCITE™ 8002.600 Polystyrene Film is a black, medium gloss, low orientation film designed for use in hot roll lamination applications to polystyrene foam and sheet.
Available in thicknesses of 0.8 - 2.5 mil (20 - 64 microns)
Compliant with U.S. FDA 21 CFR 177.1640

General Information			
Agency Ratings	FDA 21 CFR 177.1640		
Forms	Film		
Films	Nominal Value	Unit	Test Method
Film Thickness - Tested	25	µm	
Film Thickness - Recommended / Available	0.8 - 2.5 mil (20 - 64 µ)		
Tensile Elongation - MD (Break, 25 µm)	45	%	ASTM D882
Yield (25.0 µm)	37.5	m ² /kg	ASTM D4321
Optical	Nominal Value		Test Method
Gloss (60°, 25.0 µm)	50		ASTM D2457

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China


WECHAT