

# DeWAL DW 405 BNC

Ultra High Molecular Weight Polyethylene

DeWAL Industries

## Message:

DW 405 BNC Film is skived from UHMW (Ultra High Molecular Weight Polyethylene) that has been compounded with a small amount of carbon to render it black. The carbon also provides UV resistance.

DW 405 BNC is used as a wear surface where high abrasion resistance is required, such as the outer covering of hoses for severe service applications. It is also used as an anti-squeak tape for automotive and other mechanical applications.

General Information			
Features	Good Abrasion Resistance		
	Good UV Resistance		
	Good Wear Resistance		
	Ultra High Molecular Weight		
Uses	Automotive Applications		
	Hose		
	Tape		
Forms	Film		
Physical	Nominal Value	Unit	
Thickness	76.2 to 1016.0	µm	
Backing Material	Black Non-Conductive UHMW-PE		
Core ID	7.62	cm	
Maximum Roll OD	356	mm	
Width	6.35 to 762	mm	
Films	Nominal Value	Unit	Test Method
Tensile Strength - MD (Yield)	34.5	MPa	ASTM D882
Tensile Elongation - MD (Break)	250	%	ASTM D882
Thermal	Nominal Value	Unit	
Continuous Use Temperature	93.3	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT