SILPURAN® 8630/60

Silicone

Wacker Chemie AG

Message:

Silicone Rubber, HTV Catheters, Pharmaceuticals & Healthcare Medical Tubing, Pharmaceuticals & Healthcare

General Information										
Features	Biocompatible									
	BPA Free Breathable									
					Good Chemical Resistance					
	Good Flexibility									
	Good Sterilizability Good Thermal Stability									
						High Gas Permeability				
	High Heat Resistance High Purity Low to No Odor Low to No Water Absorption Non-Toxic									
							Steam Resistant			
						Uses	Body Implants			
							Medical Devices			
	Medical/Healthcare Applications									
	Pharmaceuticals									
Agency Ratings	ISO 10993									
	USP Class VI									
Processing Method	Extrusion									
Uncured Properties	Nominal Value	Unit	Test Method							
Color	Clear/Transparent									
Density	1.15	g/cm³	ISO 1183							
Cured Properties	Nominal Value	Unit	Test Method							
Shore Hardness (Shore A)	60		DIN 53505							
Tensile Strength	8.00	МРа	DIN 53504							
Tensile Elongation at Break	510	%	DIN 53504							
Compression Set	17	%	DIN ISO 815-B							

Tear Strength	41.0	kN/m	ASTM D624B
Rebound Resilience	53 to 58	%	DIN 53512

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

