

Daploy™ WE100HMS

Polypropylene Homopolymer

Borealis AG

Message:

Daploy WE100HMS is a structurally isomeric modified propylene homopolymer.

Daploy WE100HMS is intended to be used as modifier in PP coating grades to improve processing and reduce neck in

General Information			
Features	Good Processability		
	Good Thermal Stability		
	High Strength		
	Homopolymer		
	Recyclable Material		
Uses	Appliances		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	10	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Modulus	2000	MPa	ISO 527-2
Fill Analysis	Nominal Value	Unit	Test Method
Melt Extensibility	250	mm/sec	Internal Method
Melt Strength	7.0	cN	Internal Method

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT