

Shandong PP PGF6301

Polypropylene

Shandong Dongchen Engineering Plastics Co., Ltd.

Message:

Shandong PP PGF6301 is a Polypropylene material filled with 30% glass fiber. It is available in Asia Pacific.

Important attributes of Shandong PP PGF6301 are:

Flame Rated

Flame Retardant

Good Processability

Typical applications include:

Appliances

Electrical/Electronic Applications

General Information	
Filler / Reinforcement	Glass Fiber,30% Filler by Weight
Additive	Flame Retardant
Features	Flame Retardant
	Good Processability
Uses	Appliances
	Electrical/Electronic Applications

Mechanical	Nominal Value	Unit
Tensile Stress (Yield)	60.0	MPa
Tensile Strain (Break)	3.0	%
Flexural Modulus	4500	MPa
Flexural Stress	90.0	MPa
Impact	Nominal Value	Unit
Charpy Notched Impact Strength	10	kJ/m ²
Charpy Unnotched Impact Strength	30	kJ/m ²
Flammability	Nominal Value	Test Method
Flame Rating	V-0	UL 94

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT