Koylene ADL-CP AMI120N

Polypropylene Impact Copolymer

Reliance Industries Limited

Message:

Koylene ADL-CP AMI120N is a Polypropylene Impact Copolymer (PP Impact Copolymer) product. It is available in Asia Pacific. Typical application: Containers. Primary characteristic: copolymer.

General Information			
Features	Block Copolymer		
Uses	Thin-walled Containers		
Forms	Granules		
Physical	Nominal Value	Unit	Test Method
Density	0.905	g/cm³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16	5		
kg)	12	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	25.5	MPa	ASTM D638
Tensile Elongation (Yield)	12	%	ASTM D638
Flexural Modulus	1150	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	69	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Vicat Softening Temperature	150	°C	ASTM D1525

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

