

Adstif HA748L

Polypropylene Homopolymer
LyondellBasell Industries

Message:

Developmental Grade Adstif HA748L is a polypropylene homopolymer manufactured using the Spheripol process. It has very good long term thermal stability, good surface hardness, suitable for injection molding. Potential end use applications include housewares and electric appliances. It can also be evaluated for automotive and other compounds in which high rigidity and very good long term thermal stability are required

General Information			
Features	Good Thermal Aging Resistance		
	High Stiffness		
	Homopolymer		
Uses	Appliances		
	Automotive Applications		
	Household Goods		
Processing Method	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Density	0.900	g/cm ³	ASTM D1505
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	6.0	g/10 min	ASTM D1238
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (R-Scale)	110		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	39.2	MPa	ASTM D638
Tensile Elongation (Yield)	6.0	%	ASTM D638
Flexural Modulus	2210	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	44	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load (0.45 MPa, Unannealed)	130	°C	ASTM D648

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

