Huafon JF-P-8465 / JF-I-4419

Polyurethane (Polyester based)

Huafon Group Co., Ltd.

Message:

Characteristics: Medium hardness. transparent materials. Applications: For transparent shoes and translucent soles.

General Information			
Additive	Unspecified Additive		
Features	Medium Hardness		
Uses	Footwear		
Forms	Liquid		
Physical	Nominal Value	Unit	
Density ¹	0.900 to 1.20	g/cm ³	
Hardness	Nominal Value	Unit	
Hardness			
Asker A : 23°C	55.0 to 65.0		
Asker C : 23°C	70.0 to 75.0		
Thermoset	Nominal Value	Unit	
Thermoset Components			
Part A	Mix Ratio by Weight: 100		
Part B	Mix Ratio by Weight: 50 to 52		
Uncured Properties	Nominal Value	Unit	
Color ²	Clear/Transparent		
Density	•		
40°C ³	1.14 to 1.18	g/cm ³	
40°C ⁴	1.18 to 1.20	g/cm ³	
Viscosity			
40°C ⁵	0.25 to 0.35	Pa·s	
40°C ⁶	1.2 to 1.6	Pa·s	
Cured Properties	Nominal Value	Unit	
Tensile Strength	> 10.0	МРа	
Tensile Elongation at Break	> 550	%	
Tear Strength	> 40.0	kN/m	
NOTE			
1.	Molded Density		
2.	Part B		
3.	Part A		
4.	Part B		
5.	Part B		

Part A

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

