

Acculam™ Phenolfab Canvas

Phenolic

Accurate Plastics, Inc.

Message:

Acculam® Phenolfab CYBS is a laminate sheet comprised of a phenolic resin binder and woven canvas (cotton) substrate with graphite added to enhance self-lubrication.

This material is characterized by good mechanical properties and toughness. It has similar mechanical properties to C/CE. It is not intended for applications needing electrical resistance. It has good machining qualities and good wear resistance

General Information			
Filler / Reinforcement	Organic		
Features	General Purpose		
	Good Wear Resistance		
	Machinable		
Uses	Laminates		
	Sheet		
Forms	Sheet		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.36	g/cm ³	ASTM D792
Water Absorption (24 hr, 3.18 mm)	< 1.6	%	ASTM D570
Hardness	Nominal Value	Unit	Test Method
Rockwell Hardness (M-Scale)	105		ASTM D785
Mechanical	Nominal Value	Unit	Test Method
Flexural Strength			ASTM D790
3.18 mm ¹	> 110	MPa	
3.18 mm ²	> 117	MPa	
Compressive Strength ³	269	MPa	ASTM D695
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact			ASTM D256
-- ⁴	> 75	J/m	
-- ⁵	> 85	J/m	
Thermal	Nominal Value	Unit	
Temperature Index	125	°C	
Bond Strength	> 820000	g	
NOTE			
1.	CW-A		
2.	LW-A		
3.	Flatwise		
4.	CW		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

