

# Etinox® ER-B121

Rigid Polyvinyl Chloride

Ercros, S.A.

## Message:

Etinox® ER-B121 is a Rigid Polyvinyl Chloride product. It can be processed by extrusion and is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America. Primary characteristic: flame rated.

| General Information         |               |             |             |
|-----------------------------|---------------|-------------|-------------|
| Processing Method           | Extrusion     |             |             |
| Physical                    | Nominal Value | Unit        | Test Method |
| Density (23°C)              | 1.52          | g/cm³       | ISO 1183    |
| Mechanical                  | Nominal Value | Unit        | Test Method |
| Tensile Stress              | 44.1          | MPa         | ISO 527-2   |
| Tensile Strain (Break)      | 140           | %           | ISO 527-2   |
| Thermal                     | Nominal Value | Unit        | Test Method |
| Vicat Softening Temperature | 83.0          | °C          | ISO 306/B   |
| Flammability                | Nominal Value | Test Method |             |
| Flame Rating                | V-0           | UL 94       |             |

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT