## New-prene<sup>™</sup> 6155N

## Polypropylene + EPDM Rubber

Total Polymer Vision (Suzhou) Co., LTD

## Message:

New-prene<sup>™</sup> 6155N is a Polypropylene + EPDM Rubber (PP+EPDM) product. It is available in Africa & Middle East, Asia Pacific, Europe, Latin America, or North America.

General Information			
Appearance	Natural Color		
Forms	Pellets		
Hardness	Nominal Value		Test Method
Durometer Hardness (Shore A)	55		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Break)	4.50	MPa	ASTM D412
Tensile Elongation (Break)	350	%	ASTM D412
Tear Strength	20.0	kN/m	ASTM D624
Compression Set (70°C, 22 hr)	30	%	ASTM D395

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

