

# Baoding 6185B

Thermoplastic Polyurethane Elastomer

Baoding Bangtai Polymeric New-Materials Co.,Ltd

## Message:

Properties: Hot melt adhesive film, especially has great bonding capacity with TPU, PVC, NYLON, leather, polyester and fabric. Excellent initial bonding strength, good solvent solubility, strong crystallization, low thermoplasticity, can be used as a mono-component adhesive or with a crosslinking agent. We can customize different viscosities for each grade.

Applications: Clothes, Shoes, Tents, Low-temp toe puff, Luggages, etc.

General Information		
Features	Bondability	
	Good Adhesion	
Uses	Adhesives	
	Consumer Applications	
	Footwear	
	Luggage	
Appearance	Clear/Transparent	
Physical	Nominal Value	Unit
Density	1.18 to 1.22	g/cm <sup>3</sup>
Melt Mass-Flow Rate (MFR) (150°C/2.16 kg)	5.0 to 15	g/10 min
Hardness	Nominal Value	Unit
Shore Hardness (Shore A)	83 to 87	
Thermal	Nominal Value	Unit
Melting Temperature	115 to 125	°C

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT