

Magnobond 6155

Epoxy; Epoxide

Magnolia Plastics, Inc.

Message:

Magnobond 6155 is an Epoxy; Epoxide (Epoxy) product. It is available in North America. Typical application: Adhesives/Tapes.

General Information			
Uses	Adhesives		
Forms	Liquid		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.988	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore D)	72		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Compressive Modulus	2080	MPa	ASTM D695
Compressive Strength	20.7	MPa	ASTM D695
Shear Strength	10.5	MPa	ASTM D732
Thermoset	Nominal Value	Unit	Test Method
Thermoset Components			
Hardener	Mix Ratio by Weight: 35		
Resin	Mix Ratio by Weight: 100		
Pot Life (25°C)	40	min	
Shelf Life	52	wk	
Thermoset Mix Viscosity (25°C)	42000	cP	ASTM D2393
Demold Time (25°C)	10000	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT