Sinpolene MBW2422

Low Density Polyethylene

Teknor Apex Asia Pacific PTE. LTD.

Message:

Sinpolene MBW2422 is a polyethylene-based pure white masterbatch designed specifically for use in tubular film blowing, blow moulding and co-extrusion of polyolefins. With its extremely high pigment loading, Sinpolene MBW2422 offers high colouring value with excellent quality. The excellent performance of this masterbatch is attributed by specially selected high performance, fine crystal size rutile titanium dioxide. CHARACTERISTICS

Easy processing

Good dispersion

High opacifying power

Excellent whiteness

General Information	
Additive	Titanium dioxide (TiO2) (75%)
Uses	Films
	Sheet
Appearance	White
Forms	Particle
Processing Method	Blow film
	Blow molding
	Sheet extrusion molding
	Injection molding

Physical	Nominal Value	Unit	Test Method	
Melt Mass-Flow Rate (MFR) (190°C/2.1 kg)	5.0 - 15	g/10 min	ASTM D1238	
Moisture Content		%	ASTM D3030	
Additional Information				

Recommended dosage: 3 to 10%

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

