

# PHOENIX™ 16652

Thermoplastic Vulcanizate

Phon Tech Industrial Company

## Message:

PHOENIX™ 16652 is a Thermoplastic Vulcanizate (TPV) material. It is available in Asia Pacific.

General Information			
Appearance	White		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	0.920 to 0.980	g/cm <sup>3</sup>	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness (Shore A)	62 to 68		ASTM D2240
Elastomers	Nominal Value	Unit	Test Method
Tensile Strength (Break)	7.70	MPa	ASTM D412
Tensile Elongation (Break)	440	%	ASTM D412
Tear Strength <sup>1</sup>	40.3	kN/m	ASTM D624
NOTE			
1.	Die C		

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

