

# TITANEX® HC2581B

High Density Polyethylene

Lotte Chemical Titan (M) Sdn. Bhd.

## Message:

TITANEX® HC2581B is a High Density Polyethylene material. It is available in Asia Pacific for extrusion coating or film extrusion. Primary attribute of TITANEX® HC2581B: Heat Stabilizer.

Typical applications include:

Coating Applications

Film

Hose/Tubing

Wire & Cable

General Information	
Additive	Heat Stabilizer
Features	Heat Stabilized
Uses	Film
	Pipe Coatings
	Tubing
	Wire Jacketing
Forms	Pellets
Processing Method	Extrusion Coating
	Film Extrusion

Physical	Nominal Value	Unit	Test Method
Density	0.951	g/cm <sup>3</sup>	ASTM D1505
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	0.25	g/10 min	ASTM D1238

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

## Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT