

Hipolyene 6251 Y

Thermoplastic Polyolefin Elastomer

Zylog Plastalloys

Message:

Hipolyene 6251 Y is a Thermoplastic Polyolefin Elastomer (TPO (POE)) material. It is available in Africa & Middle East or Europe.

Typical application of Hipolyene 6251 Y: Automotive

General Information			
Uses	Automotive Interior Parts		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.10	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (230°C/2.16 kg)	10	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield)	200	MPa	ASTM D638
Tensile Elongation (Break)	30	%	ASTM D638
Flexural Modulus	21500	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact	12	J/m	ASTM D256

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT