ANYPOL SE-300LL

Expanded Polystyrene

SH Energy & Chemical

Message:

ANYPOL EPS Resin is an expandable bead, which contains a blowing agent. According to the applications, it is divided into Self-extinguishable & General Purpose Grade and ANYPOL EPS Resin is an environmentally friendly product which it is possible to satisfy the customer's requriements immediately for special grades since the Production Tehnology of ANYPOL EPS Resin has been developed by our own R&D.

It acquired American UL(UL94HF-1) Standard, Flame Retardant Standard as self -extinguishing, environmentally intimate, future-oriented EPS suitable for insulation plate panel and shock-absorbing packing material that has a blowing agent content below 5% and good expansion ratio & rate. Properties:

Short aging time

Good molding process

Short cycle time and good fusion

Low thermal conductivity and good strength

General Information		
Additive	Blowing Agent (< 5%)	
Features	Expandable	
	Good Processability	
	Good Strength	
	Self Extinguishing	
	Thermally Conductive	
Uses	Insulation	
	Packaging	
Physical	Nominal Value	Unit
Density	0.0250 to 0.0400	g/cm³
Additional Information	Nominal Value	Unit
Bead Size	500.0 to 680.0	μm

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519 Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

