

Ablebond 968-2

Epoxy; Epoxide
Henkel Ablestik

Message:

Ablebond 968-2 is an Epoxy; Epoxide (Epoxy) material. It is available in North America.
Important attributes of Ablebond 968-2 are:
High Purity
Insulating
Typical application of Ablebond 968-2: Adhesives/Tapes

General Information			
Features	Electrically Insulating		
	High Purity		
Uses	Adhesives		
Forms	Paste		
Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	4.0E+14	ohms·cm	ASTM D257
Thermoset	Nominal Value	Unit	
Pot Life (23°C)	20000	min	
Shelf Life (5°C)	13	wk	
Demold Time			
125°C	120	min	
150°C	60	min	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material


Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT