

# Keliren® CPE402

Chlorinated Polyethylene

Hangzhou Keli Chemical Co., Ltd.

## Message:

Keliren® Chlorinated Polyethylene(CPE) thermoplastic resins are widely used as impact modifiers in PVC extrusion and injection molding applications, especially in products such as siding, window profiles and pipe. The low dosage levels of Keliren® resins with rigid PVC resins can significantly improve impact strength and also act as a processing aid. In addition to offering attributes such as good chemical resistance, excellent low temperature properties, high filler level acceptance and excellent compatibility with a broad range of formulation ingredients, Keliren® resins offer excellent resistance to weathering in a properly formulated compound.

Application: Impact modifier in translucent applications Flame retardant

Performance: High impact strength and good flame resistance

General Information			
Features	Flame Retardant		
	Good Abrasion Resistance		
	Good Chemical Resistance		
	Good Weather Resistance		
	High Impact Resistance		
	Low Temperature Resistant		
Uses	Additive		
Physical	Nominal Value	Unit	Test Method
Chlorine Content	39.0 to 41.0	wt%	ISO 7725
Hardness	Nominal Value	Unit	Test Method
Shore Hardness (Shore A)	< 57		ISO 7619
Elastomers	Nominal Value	Unit	Test Method
Tensile Stress (Break)	> 8.00	MPa	ISO 37

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT