

TABOND 2004

Ethylene Vinyl Acetate Copolymer
SILON s.ro

Message:
TABOND 2004 is a copolymer modified with maleic anhydride functional groups.

General Information	
Features	Copolymer
	Durable
	Good Adhesion
Uses	Adhesives
	Blow Molding Applications
	Bonding
	Metal Bonding
	Plastics Modification
	Tubing
Appearance	White
Forms	Pellets
Processing Method	Blow Molding
	Coextrusion

Physical	Nominal Value	Unit	
Density	0.912	g/cm ³	
Melt Mass-Flow Rate (MFR) (190°C/2.16 kg)	1.4	g/10 min	
Hardness	Nominal Value	Unit	
Shore Hardness (Shore D)	38		
Thermal	Nominal Value	Unit	Test Method
Melting Temperature	98.0	°C	DSC

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection.All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

