Sylvin 2921-70 Natural

Polyvinyl Chloride

Sylvin Technologies Incorporated

Durometer Hardness (Shore A, 10 sec)

Message:

Mechanical

Elastomers

Tear Strength Thermal

Melting Temperature

Tensile Strength

Tensile Elongation (Break)

Sylvin 2921-70 Natural Is A Vinyl Compound Formulated With FDA Sanctioned Ingredients For Extrusion Or Injection Molding Applications.

General Information			
Agency Ratings	FDA Unspecified Rating		
Appearance	Natural Color		
Processing Method	Extrusion		
	Injection Molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.45	g/cm ³	ASTM D792
Hardness	Nominal Value	Unit	Test Method

Unit

MPa

Unit

kN/m

Unit

°C

%

ASTM D2240

Test Method

ASTM D638

ASTM D638

Test Method

ASTM D624

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is
strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any
infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

70

10.3

350

35.0

Nominal Value

Nominal Value

Nominal Value

160 to 171

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

