Daelim Po1y® PP-246

Polypropylene Impact Copolymer DAELIM INDUSTRIAL CO., LTD.

Message:

Daelim Po1y®PP-246 is a polypropylene impact copolymer (PP Impact Copoly) product. It can be processed by injection molding and is available in the Asia-Pacific region. Daelim Po1y®PP-246 application areas include electrical/electronic applications, furniture, home applications and containers. Features include:

Copolymer anti-warping Good stiffness Good toughness

Impact resistance

General Information					
Features	Block Copolymer				
	Low warpage				
	Rigid, good				
	Low temperature impact resistance				
	Good toughness				
	Narrow molecular weight distribution				
Uses	Electrical/Electronic Applications				
	Furniture				
	Household goods				
	Container				
Forms	Particle				
Processing Method	Injection molding	Injection molding			
Physical	Nominal Value	Unit	Test Method		
Density	0.900	g/cm³	ASTM D1505		
Melt Mass-Flow Rate (MFR) (230°C/2					
kg)	21	g/10 min	ASTM D1238		
Hardness	Nominal Value	Unit	Test Method		
Rockwell Hardness (R-Scale)	90		ASTM D785		
Mechanical	Nominal Value	Unit	Test Method		
Tensile Strength (Yield)	28.4	MPa	ASTM D638		
Tensile Elongation (Yield)	20	%	ASTM D638		
Flexural Modulus	1370	MPa	ASTM D790		
Impact	Nominal Value	Unit	Test Method		
Notched Izod Impact			ASTM D256		
-20°C	39	J/m	ASTM D256		
23°C	78	J/m	ASTM D256		
Thermal	Nominal Value	Unit	Test Method		

Deflection Temperature Under Load (0.45				
MPa, Unannealed)	110	°C	ASTM D648	
Vicat Softening Temperature	150	°C	ASTM D1525	
Additional Information				

Accelerated Oven Aging in Air, ASTM D3012, Forced Circulation at 150°C: 360 hours

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

