

# POLYCOMPO PE 3530

Low Density Polyethylene

POLYCOMPO Co.,Ltd.

## Message:

POLYCOMPO PE 3530 is a Low Density Polyethylene product. It can be processed by extrusion and is available in Asia Pacific. Primary characteristic: good aesthetics.

General Information			
Features	Good Surface Finish		
Forms	Pellets		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Density	0.924	g/cm <sup>3</sup>	ISO 1183
Melt Mass-Flow Rate (MFR)	2.3	g/10 min	ISO 1133
Mechanical	Nominal Value	Unit	Test Method
Tensile Stress (Break, Injection Molded)	19.0	MPa	ISO 527-2
Tensile Strain (Break, Injection Molded)	400	%	ISO 527-2
Thermal	Nominal Value	Unit	Test Method
Brittleness Temperature	-76.0	°C	ASTM D746A, ISO 974
Vicat Softening Temperature	98.0	°C	ASTM D1525, ISO 306

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

## Recommended distributors for this material

### Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China



WECHAT