

NOVA PC 1023

Polycarbonate

NOVA Polymers, Inc.

Message:

NOVA PC 1023 is a polycarbonate (PC) material. This product is available in North America and is processed by injection molding.

The main features of NOVA PC 1023 are:

flame retardant/rated flame

UV stability

General Information			
Additive	UV stabilizer		
UL File Number	E143392		
Forms	Particle		
Processing Method	Injection molding		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.20	g/cm ³	ASTM D792
Melt Mass-Flow Rate (MFR) (300°C/1.2 kg)	17	g/10 min	ASTM D1238
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Yield, 3.18 mm)	62.1	MPa	ASTM D638
Flexural Modulus (3.18 mm)	2210	MPa	ASTM D790
Flexural Strength (Yield, 3.18 mm)	94.5	MPa	ASTM D790
Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	750	J/m	ASTM D256
Thermal	Nominal Value	Unit	Test Method
Deflection Temperature Under Load			ASTM D648
0.45 MPa, not annealed	138	°C	ASTM D648
1.8 MPa, not annealed	132	°C	ASTM D648
Flammability	Nominal Value		Test Method
Flame Rating			UL 94
3.18 mm	V-2		UL 94
6.35 mm	V-2		UL 94
Additional Information			
Moisture Content, ASTM D 4019-88: <0.04 %			

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533

Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

