Sylvin 83039-74 Brown 7461

Polyvinyl Chloride

Sylvin Technologies Incorporated

Message:

Sylvin 83039-74 Brown 7461 Is A Vinyl Compound Formulated For Extruded Garage Door Seals Applications.

General Information			
Features	General		
Uses	Industrial application		
	Seals		
	General		
Appearance	Brown		
Processing Method	Extrusion		
Physical	Nominal Value	Unit	Test Method
Specific Gravity	1.41	g/cm³	ASTM D792
Hardness	Nominal Value	Unit	Test Method
Durometer Hardness	Tommal value	- Crinc	ASTM D2240
Shaw A	74		ASTM D2240
Shaw A, 10 seconds	74		ASTM D2240
Mechanical	Nominal Value	Unit	Test Method
Tensile Strength (Break)	11.7	MPa	ASTM D638
Tensile Elongation (Break)	330	%	ASTM D638
Elastomers	Nominal Value	Unit	Test Method
Tear Strength	48.2	kN/m	ASTM D624
Thermal	Nominal Value	Unit	
Melting Temperature	163 - 174	°C	

The information and data on this page are provided by manufacturers and document providers. SHANGHAI SUSHENG assumes no legal liability. It is strongly recommended to verify all technical data with material suppliers before final material selection. All rights belong to the original authors. If any infringement occurs, please contact us immediately.

Recommended distributors for this material

Susheng Import & Export Trading Co.,Ltd.

Tel: +86 21 5895 8519

Phone: +86 13424755533 Email: sales@su-jiao.com

No. 215, Lianhe North Road, Fengxian District, Shanghai, China

